

BULLET INFRA-RED CAMERA

PMD3213 / PMD3220 / PMD3230



HIGHLIGHTS

- Offer resolution from 1.3 to 3MP
- Day/Night auto switch
- 1/2.7" progressive scan CMOS
- H.264 / MJPEG video compression
- Smart IR technology
- Motion detection and Tampering alarm functions
- Quad-streaming
- Weatherproof with IP66 rated
- IR covers up to 25m distance

PRIME Bullet type IP camera, is an all-in-one network camera that provides 720P, 1080P full HD and 3MP resolution. This camera is designed to suite basically any installation environments, includes indoor and outdoor. The built-in IR illuminator can covers up to 25m distance to produce clear images in no light situation. H264 and MJPEG video compression provides excellent image clarity, and efficient bandwidth and video storage. For different applications, we provide choices of different lens options from 3mm to 9mm manual vari-focal lens, or with motorised auto zoom/auto focus lens.



BULLET CAMERA

Camera Imaging Specifications

Model	PMD3213-F0309	PMD3220-F0309	PMD3230-F0309
Video Compression	H.264 (MPEG-4 Part 10/AVC) / MJPEG		
Image Sensor & Resolution	1/2.7" CMOS 1280x720@30FPS	1/2.7" CMOS 1920x1080@30FPS	1/2.7" CMOS 2048x1536@15FPS
Minimum Illumination	Color 0.2 lux / Black & White 0.02 lux		
Lens Option	Vari-focal 3-9mm, F1.5 / Motorized 3-9mm, F1.5 (optional)		
Dual Streaming	Main streaming: 1280x720	Main streaming: 1920x1080 Sub-streaming: 704x576 / 352x288	Main streaming: 2048x1536

Network

Interface	RJ-45 connector, 10/100mbps
Video Streaming	Dual Streams H.264 + H.264 / H.264 + MJPEG Quad Streams H.264 x 4 / H.264 x 3 + MJPEG
Protocol	ARP, IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF
Security/Authorization	HTTPS / IP Filter / IEEE 802.1X
Audio	One-way, Mic In
Event Notification	HTTP / FTP / SMTP
Onboard Storage	microSDHC 32GB support
Supported Web Browser	Internet Explorer (6.0+) / Chrome / Firefox / Safari
Users / Password	20 User accounts / User & Administrator

General

Audio	Two-way (Line in / Line out) Compression (G.711 / G.726)
Built-in IR Illuminator	Working Distance: up to 25m Wavelength: 850nm
Operating Temperature	-10°C ~ 50°C (14° ~ 122° F)
Humidity	10% ~ 90%, No Condensation
Dimension	ø 84 x 260 mm (ø 3.3 x 7.1 in.) ø 90 x 270 mm (ø 3.3 x 7.6 in.) w/ Sunshield
Weight	940 g
Power Source	24VAC / PoE
Regulatory	FCC / CE / RoHS

